

TITLE: METHOD OF ANALYSING GRANULAR COMPOSITION BY FLUORESCENCE ANALYSIS

FIELD OF THE INVENTION

5 The present invention relates to a method for analyzing a property of a granular composition comprising a biologically active compound by subjecting the granular composition to fluorescence analysis. The invention also relates to a method for producing a particulate product comprising subjecting the product to
10 fluorescence analysis. Further the invention relates to a granulation and/or coating apparatus suitable for preparing a granular composition comprising a biologically active compound said apparatus comprising means for fluorescence analysis.

BACKGROUND OF THE INVENTION

15 Analysis of chemical compounds in samples exploiting that some compounds (fluorophors) exhibit fluorescence when excited with light (fluorescence analysis) are well known to the art. While fluorescent analysis has its advantages in being sensitive and accurate in well-defined samples it also has serious drawbacks.
20 For example in complex samples the fluorescence of a fluorophor is often altered by other compounds present in the environment surrounding the fluorophor (known as quenching) making it difficult to use a fluorescence analysis quantitatively on complex and/or poorly defined samples. This applies especially in
25 heterogeneous or solid phase samples where also scattering of the light has to be accounted for.

During recent years developments in electronics the more sophisticated methods of fluorescent imaging using camera detectors has emerged, enabling photographing of emitted light in

fluorescing samples, so that two dimensional images showing the spatial distribution of fluorophors in the sample.

One example of fluorescence imaging of aleurone tissue for flour refinement using UV excitation is known from Dexter et al.,
5 Cereal Chemistry, vol. 70(1), 90-95, 1993.

Kaufman et al., Powder Technology, vol. 78(3), 239-246, 1994) have done *in situ* visualization of coal particle distribution in a liquid fluidised bed using fluorescence microscopy.

10 More general examples of imaging in analysis is found in Buydens et al., Analytical Chimica Acta, vol. 361(1-2), 161-176, 1998 who has reported on-line classification and multivariate image analysis on plastics in waste based on imaging in the Near Infrared Range of light.

15 Watano et al., Pharmaceutical Bulletin, vol. 48(8), 1154-1159, 2000 has reported on-line monitoring of granule growth in high shear granulation by an imaging processing system.

20 Watano et al. has in US 5,497,232 reported imaging of granule growth in a fluid bed or a pan type granulator using a photographic camera such as a CCD camera of the type used in video cameras.

SUMMARY OF THE INVENTION

The present invention relates to a method for analyzing a property of a granular composition comprising a purified
25 biologically active compound by subjecting the granular composition to fluorescence analysis. Formulation of chemical compounds into finished goods, in particular granulation, is usually required to achieve improved properties of the products, thus making them more commercially attractive. However, for
30 biologically active compounds, granulation is often compulsory to the producers because the active compound must, until being

applied in the intentional use, be separated from the surrounding environment to ensure the safe handling of the product. The amount of biologically active compound which can escape from the granulated product, e.g. in the form of dust, must be minimized to ensure that persons handling the product do not suffer any adverse effects from contact with the biologically active compound. Vice versa the active compound must be protected from the environment outside the granule to remain stabile and active once it is to be used. Once an active compound has been granulated it is known that one may further coat granules comprising biologically active compound with a coating agent which further suppress the release of active compound from the granule and further improve the stability of the active compound in the granule. Usually by increasing the thickness of the coating layer, it is possible to further improve granule properties.

One object of the invention is to provide methods, particularly in the form of an imaging system, for measuring quality parameters of a granular composition comprising a purified biologically active compound. Such a parameter may be for example the amount of active compound released from granules in the form of active dust, during or after the process for preparing the granular composition. Another parameter is for example the thickness and/or integrity of coating layers applied to the granules to suppress dust formation and increase the stability of the active compound which by the present invention could be measured during or after a process of coating of granules comprising a biologically active compound. Another object of the invention is to design a granulation apparatus and to select method setup, so that the method may be used on-line or in-line in the production of such granular compositions, and that the methods in real may time provide information about levels of dust

comprising biologically active compound during processing of the granular composition.

100534-01507
We have found that for granular compositions comprising a purified biologically active compound both active compound
5 confined in the surface regions of granules and active compound, which is present in the composition in the dust particles, e.g. as a result from release of active compound from the granules or as a result from insufficient granulation, can be evaluated by illuminating the composition with light capable of fluorescence
10 excitation of a fluorescent marker, e.g. the biologically active compound itself, and detecting emitted light from the fluorescent marker. Accordingly, the present invention provides in a first aspect a method for fluorescence analysis comprising illuminating a granular composition comprising a purified biologically active
15 compound with light capable of fluorescence excitation of a fluorescent marker comprised in the granular composition, detecting light emitted from the fluorescent marker and predicting the amount of fluorescent marker in the granular composition accessible to fluorescence excitation. The amount of
20 accessible fluorescent marker may be linked to a property of the granular composition, such as dust levels and/or coating thickness or coating integrity.

Further, in a second aspect, the invention provides a process for preparing granules comprising a purified biologically
25 active compound, a fluorescent marker and optionally auxiliary granulation agents in a granulation apparatus said process comprising the step of performing fluorescence analysis in accordance with the first aspect of the invention (*vide supra*).

Still further, in a third aspect, the invention provides a
30 granulation or coating apparatus comprising (a) a granulating or coating device comprising at least one chamber for granulating material or for coating of granulated material, (b) at least one

detector capable of detecting emitted light, (c) means for projecting a source of illuminating light in form of a beam onto a portion of the material being processed, (d) means for canalising light emitted from illuminated material to the
5 detector and (e) at least one device for selecting wavelength of the illuminating or emitted light.

Finally, in a fourth aspect the invention provides use of fluorescence analysis on granules comprising a purified biologically active compound.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1: an example of an optical arrangement, wherein
1=detectors (CCD cameras), 2=light source, 3=band pass filters,
4=dichroic mirror beam splitters, 5=lenses, 6=funnel,
15 7=fluorescing granules passing the illuminating beam of light.

Figure 2: an example of an on-line optical arrangement, wherein
1=picture showing the emitted light from the granules as recorded
by a CCD camera, 2=CCD camera, 3=light source, 4=granules on a
conveyer belt.

20 DETAILED DESCRIPTION OF THE INVENTION

Fluorescence analysis

The present invention relates, as described, to a method for performing fluorescence analysis on a granular composition comprising an active compound.

25 The first step of the method comprises illuminating the granular composition with a beam of light, which can excitate a fluorescent marker comprised in the granular composition. In this process photons from the illuminating light will be absorbed by the fluorescent marker with the result, that electrons in the

fluorescent compound gain energy and are brought into a specific increased energy level. The excited fluorescent marker will, as the electrons return to their original ground state energy level, subsequently liberate at least some of the gained energy by emitting light photons of a wavelength characteristic for the energy difference between the increased energy level and the original energy level.

The second step of the method comprises detecting the emitted light from the granular composition with a detector, capable of converting the emitted light into an electronic signal.

The third step of the method comprises processing the electronic signal to correlate the amount of emitted lights to one or more properties of the granular composition by predicting the amount of fluorescent marker in the granular composition accessible to fluorescence excitation.

The interpretation and meaning of all terms, pertaining to the basic principles of fluorescence analysis are known to the skilled person.

20 Illumination of the granular composition

The illumination of the granular composition may be carried out with any suitable light source delivering light capable of exciting the fluorescent marker in the granular composition. The light source may be e.g. a normal glow lamp, a more specialized xenon lamp or a stroboscope lamp.

The optical properties of the fluorescent marker compound may be known and to optimise the excitation of a known fluorescent marker it is preferred to select a light source delivering a substantial portion of light of wavelengths suitable for exciting the fluorescent marker. If it is desired (which it may be when using a known fluorescent marker) to avoid

or limit excitation and emission from compounds other than the fluorescent marker, which may interfere with the analysis, it may be desired to filter the beam of light, so that only light of selected wavelengths illuminates the granular composition. This
5 may be done with one or more beam splitters and one or more band pass filters, such as high and/or low band pass filters, or grate monochromators allowing only light with specific wavelengths to pass. These features are normally integrated in commercially available fluorescence analysers, e.g. from Perkin
10 Elmer, USA. It is known to the skilled person that band pass filters and monochromators will allow passage of light having wavelengths within a narrow ranges, normally within a few nm, such as 0.5-10 nm. Thus the term monochromatic light is to be understood as light having wavelengths within the narrow range
15 determined by the band pass filter or the grate monochromator.

In a particular embodiment the light illuminating the granular composition consist of 1-10 discrete monochromatic wavelengths, particularly 1-4 discrete monochromatic wavelengths. In particular the light illuminating the granular
20 composition consist of one discrete monochromatic wavelength. In the step of illuminating the granular composition an optical arrangement may suitably be employed comprising e.g. mirrors, beam splitters (such as dichroic mirrors) and/or fiber optics to project the illuminating light onto the granular composition.

25 Detection of emitted light

The emitted light may be characteristic for the fluorescent marker or for chemical groups or constituents comprised in the fluorescent marker. As the fluorescent marker usually only emit light within one or more narrow ranges of wavelengths it is
30 preferred to filter the emitted light, so that only emitted light within these ranges are allowed to reach the detector.

This may be achieved by filtering the emitted light with one or more band pass filters or monochromators as described, *supra*. This may avoid or limit the amount of emitted light from compounds other than the fluorescent marker from reaching the 5 detector and which may interfere with the analysis. Accordingly, in a particular embodiment only emitted light of 1-10 discrete monochromatic wavelengths are detected, particularly 1-4 discrete monochromatic wavelengths. In particular emitted light reaching the detector consists of one discrete monochromatic 10 wavelength.

Further, as for the illumination, in the step of detecting the emitted light an optical arrangement may suitably be employed comprising e.g. mirrors, beam splitters (such as dichroic mirrors), fiber optics, and or means for focusing the 15 emitted light (such as lenses) to project the emitted light into the detector.

A variety of detectors may be applied to detect the emitted light. The detector may be a photo multiplication type detector, a photo diode or photo diode array, a line scan camera, a CCD 20 camera, an ICCD camera or any other type suitably for detecting the emitted light. A particular detector may be a camera type detector, such as selected from the group of grey scale cameras, line scan cameras, photodiode arrays, CCD (charged Coupled Device) cameras and ICCD (Intensified CCD) cameras. In 25 particular detectors may be CCD cameras and ICCD cameras, because they are more sensitive and enable formation of 2 dimensional images, showing the spatial distribution of the light emitting granules or dust particles. This is called fluorescence imaging in terms of the skilled analyst. In a 30 particular embodiment two or more detectors may be used to record two or more selected wavelengths or two or more ranges of wavelengths simultaneously. This is desired if more than one

fluorescent marker is to be measured or if a particular fluorescent marker emits light at different wavelengths. This is particularly achieved using an optical arrangement including one or more beam splitters and two and more band pass filters or
5 monochromators. In a most particular embodiment an optical arrangement including two CCD cameras, dichroic mirrors and band pass filters and lenses as shown schematically in figure 1 is used.

Processing of detected signal

10 Conversion of the emitted light, in the detector, into an electronic signal and converting this signal into a measure, such as a number, from which a prediction of the amount of emitted light and the amount of fluorescent marker accessible to
15 excitation may be inferred, is known to the skilled person, as analysers for making fluorescence analysis are abundantly available. The prediction may suitably be made by comparing the amount of the emitted light from an unknown granular composition with data on emitted light from a granular composition of known properties, and thus predicting in the unknown granular
20 composition the amount of fluorescent marker accessible to excitation. The output of most detectors such as photo multiplication based types or some photo diode based types is an analogue signal. Most detectors such as many cameras, which comprise numerous single photo diode detectors, may have a build
25 in analogue-digital converter capable of converting the analogue signal into a digital signal, which is more suitable for computerized data processing. Depending on the fluorescent marker and property of the granular composition one wishes to link to the amount of emitted light, the digital data arising
30 from the emitted light may be subjected to processing. This processing is suitably performed in a computer system using

software designed for such processes. Such software may be the LabView software as used in the examples herein or any other software providing the necessary capabilities for performing the desired data processing to link the amount of emitted light to a property of the granular composition. The data processing may include operations such as particle counting, gauging, pattern matching (grey scale and colour), statistics, thresholds, multivariate image analysis, AMT, blob analysis, area calculation, edge detection, morphology analysis, convolution, folding and unfolding, FFT, various filtering techniques e.g. median filtering - all techniques known to the skilled analyst, which are data processing functions included in commercially available software. In the process of transferring data to a computing unit the computing unit usually have to be equipped with hardware capable of acquiring the data from the detector for storage in the computing unit. Such hardware, e.g. data acquisition cards, is well known. When using a CCD or other type of camera producing 2 dimensional images of fluorescent granules it is also advantageous to use, in the computing unit, software capable of recording the 2 dimensional images in form of discrete digital still images. Such software is known as frame grabber programs. The speed at which such software is capable of recording images usually depends on the speed of the computing unit, and of for most fluorescence analysis purposes a speed of about 15 frames per second suffices. This means that 15 two-dimensional images are recorded per second.

The granular composition

Physical properties

The granular composition of the invention is a composition comprising the biologically active compound, a fluorescent

marker, which may be the biologically active compound itself and optionally auxiliary granulation agents and coating agents processed into particles or granules. Accordingly, finished granules are the result of the processes and methods of the invention. The term "granules" are to be understood as a predominantly spherical or near spherical structure of a macromolecular size, particularly having an average size measure in the longest diameter between 20-2000 μm , more particularly between 100-1000 μm , most particularly between 200-800 μm . The spherical granules preferably have a ratio, (a):(b), between the diameter in the shortest dimension (a) and the diameter in the longest dimension (b) of the granule of between 1:1 to 1:5, particularly between 1:1 to 1:3.

The "size distribution" (PSD) of granules can be expressed in terms of the mass mean diameter of the individual particles. A mean mass diameter of D50 is the diameter at which 50% of the granules, by mass, have a smaller diameter, while 50% by mass have a larger diameter. The values D10 and D90 are the diameters at which 10% and 90%, respectively, of the granules, by mass, have a smaller diameter than the value in question. The "SPAN" indicates the breadth of the PSD and is expressed as:

$(D90-D10)/D50$. For purposes of the present invention, the PSD of granules after granulation is normally as narrow as possible. Use of fluorescence analysis, in accordance with the present invention, for controlling the granulation process may aid in lowering of the PSD, and the SPAN of the granular composition after granulation is therefore particularly less than about 2.5, particularly less than about 2.0, more particularly less than about 1.5, and most particularly less than about 1.0.

The granules are particularly coated with a coating agent forming a, particularly homogenous, coherent and continuous, layer around the granules. The term coating agent as used herein

is to be understood as single coating compound or a mixture of coating compounds. Coated granules thus consist of a granule core and a granule coating. Particularly the coating layer is relatively thick in order to further reduce dusting and improve stability of the biologically active compound. The coating thickness may be described by the ratio between the average diameter of a coated granule core and the average diameter of an uncoated granule core (hereinafter abbreviated D_G/D_C), i.e. the average diameter of the coated granule divided by the average diameter of the granule core only. If for example a granule core having a diameter of 100 μm is coated with a coating layer 200 μm thick, the granule would have a diameter of $(200+100+200)=500$ μm and D_G/D_C is $500 \mu\text{m}/100 \mu\text{m} = 5$. Coated granules of the invention particularly have a D_G/D_C of at least 1.1, which means that the thickness of the coating is at least 5% of the average granule core diameter. A more particular D_G/D_C is at least 1.5, more particularly at least 2, more particularly at least 2.5, more particularly at least 3, most particularly at least 4. D_G/D_C is however particularly below about 100, particularly below about 50, more particularly below 25, and most particularly below 10. A most particular range for D_G/D_C is about 4 to about 6.

Furthermore, in the present invention the coating is substantially enzyme-free, The term "substantially enzyme free " as used herein about a coating means that there is less than 5 mg of enzyme per gram coating agent.

Considering the materials making up granules of the invention (vide infra) these are, as opposed to transparent materials such as glass, in general impassable to visual light, e.g. a person will usually not be able to see-through the granules. However, when subjecting granules comprising a biologically active compound of the art to excitation light we

have discovered that such excitation light may penetrate the surface of the granule and excitate a suitable fluorescent compound present at and/or near the surface of the granule and that emitted light from such fluorescent compound may escape the
5 granule so that it can be received by a detector.

Further, the content of moisture in the granules is typically be less than 20(w/w)%, particularly less than 15(w/w)%, more particularly less than 10(w/w)%, such as in the range of 4 to 8(w/w)%.

10

Construction

The granules may be constructed by any granulation method known in the art.

The construction of the granules of the invention may be
15 divided into the following non-exhaustive categories:

a) Spray dried granules, wherein a liquid solution containing the biologically active compound is atomised in a spray dryer to form small droplets which during their way down the dryer dry to
20 form a granular material comprising the biologically active compound. Very small granules can be produced this way (Michael S. Showell (editor); *Powdered detergents*; Surfactant Science Series; 1998; vol. 71; page 140-142; Marcel Dekker). For these granules the biologically active compound is intimately mixed
25 with any other auxiliary granulation agents present in the liquid solution.

b) Layered granules, wherein the biologically active compound is coated as a layer around a pre-formed core particle, wherein an
30 solution containing the biologically active compound, and particularly auxiliary granulation agents, is atomised,

typically in a fluid bed apparatus wherein the pre-formed core particles are fluidised, and the solution of biologically active compound adheres to the core particles and dries up to leave a layer of dry biologically active compound on the surface of the core particle. Granules of a desired size can be obtained this way if a useful core particle of the desired size can be found. This type of granules is described in e.g. WO 97/23606

c) Absorbed core granules, wherein rather than coating the biologically active compound as a layer around the core, the biologically active compound is absorbed onto and/or into the surface of the core. Such a process is described in WO 97/39116.

d) Extruded or pelletized granules, wherein a paste containing the biologically active compound is pressed into granules in a mould or under pressure is extruded through a small opening and cut into granules which are subsequently dried. Such granules usually have a considerable size because of the material in which the extrusion opening is made (usually a plate with bore holes) sets a limit on the allowable pressure drop over the extrusion opening. Also, very high extrusion pressures when using a small opening increase heat generation in the paste, which may be harmful to the biologically active compound. (Michael S. Showell (editor); *Powdered detergents*; Surfactant Science Series; 1998; vol. 71; page 140-142; Marcel Dekker)

e) Spray cooled granules, wherein a powder of biologically active compound is suspended in molten wax and the suspension is sprayed, e.g. through a rotating disk atomiser, into a cooling chamber where the droplets quickly solidify (Michael S. Showell (editor); *Powdered detergents*; Surfactant Science Series; 1998; vol. 71; page 140-142; Marcel Dekker). For these granules the

biologically active compound is intimately mixed with the wax instead of being concentrated on its surface. Also US 4,016,040 and US 4,713,245 are documents relating to this technique

5 f) High shear mixer granules, wherein a liquid containing the biologically active compound is added to a dry powder composition of auxiliary granulation agent. The liquid and the powder in a suitable proportion are mixed and as the moisture of the liquid is absorbed in the dry powder, the components of the
10 dry powder will start to adhere and agglomerate and granules will build up, forming granules comprising the biologically active compound. For these granules the active compound is intimately mixed with the auxiliary granulation agents. Such a process is described in US 4,106,991 (NOVO NORDISK) and related
15 documents EP 170360 B1 (NOVO NORDISK), EP 304332 B1 (NOVO NORDISK), EP 304331 (NOVO NORDISK), WO 90/09440 (NOVO NORDISK) and WO 90/09428 (NOVO NORDISK).

Dust particles in granular compositions

20 Dust particles, which may be present in a granular composition, may be characterised in that they are fragments of whole granules, which usually have a considerably smaller size than the granules and do not possess the characteristic spherical shape of the granules. Dust particles typically have an
25 irregular non-spherical and abrupt structure such as rod or flake shaped. Dust particles are typically much smaller than the average size of granules, and most dust particles are, depending on the granular composition less than 20 μm in diameter.

Dust particles being fragments of whole granules possess
30 the same in-transparency and usually have about the same moisture content as intact granules, *supra*.

Compounds in the granular composition

Biologically active compounds

10057494-01E03
The granular composition of the invention comprises a biologically active compound, in particular a purified
5 biologically active compound. The term biologically active compound as used herein is to be understood as any compound, which is active in a biological system such as compounds, which interfere with and/or modifies biological pathways or biological reactions. The term "purified" as used herein is to be understood
10 as biologically active compounds, which before granulation has been subjected to one or more purification step to remove e.g. excess material and/or to concentrate the active compound. In the case the active compound is prepared by a microbiological fermentation process purification particularly includes step
15 selected from filtering, ultra-filtration, flocculation, sedimentation, evaporation, extraction and the like, to remove biomass and other undesired matter including water to yield a mixture which is enriched in the biologically active compound.

20 Biologically active compounds include among others organic compounds such as bio-catalysts, therapeutic agents, herbicides, pesticides and fungicides. In particular the biologically active compound is producible by fermenting a microorganism producing the active compound.

In particular compounds are those among proteins and
25 peptides, more particularly catalytic proteins, i.e. enzymes, because proteins such as enzymes are used in vast volumes in the industry and are known to cause adverse allergy reactions in humans or animal when exposed to such proteins. Furthermore, enzymes are widely used in household products such as detergents
30 for removing soil of a biological origin, and many industrial processes involves human handling of the enzymes. The enzyme may

be any enzyme for which it is desired to separate the enzyme from the surrounding environment through granulation of the enzymes.

The enzyme classification employed in the present specification with claims is in accordance with *Recommendations (1992) of the Nomenclature Committee of the International Union of Biochemistry and Molecular Biology*, Academic Press, Inc., 1992.

Accordingly the types of enzymes which may appropriately be incorporated in granules of the invention include oxidoreductases (EC 1.-.-.-), transferases (EC 2.-.-.-), hydrolases (EC 3.-.-.-), lyases (EC 4.-.-.-), isomerases (EC 5.-.-.-) and ligases (EC 6.-.-.-).

Particular oxidoreductases in the context of the invention are peroxidases (EC 1.11.1), laccases (EC 1.10.3.2) and glucose oxidases (EC 1.1.3.4)], while particular transferases are transferases in any of the following sub-classes:

- a) Transferases transferring one-carbon groups (EC 2.1);
- b) transferases transferring aldehyde or ketone residues (EC 2.2); acyltransferases (EC 2.3);
- c) glycosyltransferases (EC 2.4);
- d) transferases transferring alkyl or aryl groups, other than methyl groups (EC 2.5); and
- e) transferases transferring nitrogenous groups (EC 2.6).

A most particular type of transferase in the context of the invention is a transglutaminase (protein-glutamine γ -glutamyltransferase; EC 2.3.2.13).

Further examples of suitable transglutaminases are described in WO 96/06931 (Novo Nordisk A/S).

Particular hydrolases in the context of the invention are: Carboxylic ester hydrolases (EC 3.1.1.-) such as lipases (EC 3.1.1.3); phytases (EC 3.1.3.-), e.g. 3-phytases (EC 3.1.3.8) and 6-phytases (EC 3.1.3.26); glycosidases (EC 3.2, which fall
5 within a group denoted herein as "carbohydases"), such as α -amylases (EC 3.2.1.1); peptidases (EC 3.4, also known as proteases); and other carbonyl hydrolases].

In the present context, the term "carbohydrase" is used to denote not only enzymes capable of breaking down carbohydrate
10 chains (e.g. starches) of especially five- and six-membered ring structures (i.e. glycosidases, EC 3.2), but also enzymes capable of isomerizing carbohydrates, e.g. six-membered ring structures such as D-glucose to five-membered ring structures such as D-fructose.

15 Carbohydases of relevance include the following (EC numbers in parentheses):

alpha-amylases (3.2.1.1), beta-amylases (3.2.1.2), glucan 1,4-alpha-glucosidases (3.2.1.3), cellulases (3.2.1.4), endo-1,3(4)-beta-glucanases (3.2.1.6), endo-1,4-beta-xylanases (3.2.1.8),
20 dextranases (3.2.1.11), chitinases (3.2.1.14), polygalacturonases (3.2.1.15), lysozymes (3.2.1.17), beta-glucosidases (3.2.1.21), alpha-galactosidases (3.2.1.22), beta-galactosidases (3.2.1.23), amylo-1,6-glucosidases (3.2.1.33),
25 xylan 1,4-beta-xylosidases (3.2.1.37), glucan endo-1,3-beta-D-glucosidases (3.2.1.39), alpha-dextrin endo-1,6-alpha-glucosidases (3.2.1.41), sucrose alpha-glucosidases (3.2.1.48),
glucan endo-1,3-alpha-glucosidases (3.2.1.59), glucan 1,4-beta-glucosidases (3.2.1.74), glucan endo-1,6-beta-glucosidases (3.2.1.75), arabinan endo-1,5-alpha-L-arabinosidases (3.2.1.99),
30 lactases (3.2.1.108), chitosanases (3.2.1.132) and xylose isomerases (5.3.1.5).

Examples of commercially available oxidoreductases (EC 1.-
.-.-) include GLUZYME™ (enzyme available from Novo Nordisk A/S).

Examples of commercially available proteases (peptidases)
include KANNASE™, EVERLASE™, ESPERASE™, ALCALASE™, NEUTRASE™,
5 DURAZYM™, SAVINASE™, PYRASE™, PANCREATIC TRYPSIN NOVO (PTN),
BIO-FEED™ PRO and CLEAR-LENS™ PRO (all available from Novo
Nordisk A/S, Bagsvaerd, Denmark).

Other commercially available proteases include MAXATASE™,
MAXACAL™, MAXAPEM™, OPTICLEAN™ and PURAFECT™ (available from
10 Genencor International Inc. or Gist-Brocades).

Examples of commercially available lipases include
LIPOPRIME™ LIPOLASE™, LIPOLASE™ ULTRA, LIPOZYME™, PALATASE™,
NOVOZYM™ 435 and LECITASE™ (all available from Novo Nordisk
A/S).

15 Other commercially available lipases include LUMAFast™
(*Pseudomonas mendocina* lipase from Genencor International Inc.);
LIPOMAX™ (*Ps. pseudoalcaligenes* lipase from Gist-
Brocades/Genencor Int. Inc.; and *Bacillus* sp. lipase from Solvay
enzymes).

20 Examples of commercially available carbohydrases include
ALPHA-GAL™, BIO-FEED™ ALPHA, BIO-FEED™ BETA, BIO-FEED™ PLUS,
BIO-FEED™ PLUS, NOVOZYME™ 188, CELLUCLAST™, CELLUSOFT™,
CEREMYL™, CITROZYM™, DENIMAX™, DEZYME™, DEXTROZYME™, FINIZYM™,
FUNGAMYL™, GAMANASE™, GLUCANEX™, LACTOZYM™, MALTOGENASE™,
25 PENTOPAN™, PECTINEX™, PROMOZYME™, PULPZYME™, NOVAMYL™,
TERMAMYL™, AMG™ (Amyloglucosidase Novo), MALTOGENASE™,
SWEETZYME™ and AQUAZYM™ (all available from Novo Nordisk A/S).
Further carbohydrases are available from other suppliers.

The amount of enzyme to be incorporated in a granule of the invention will depend on the intended use of the granule. For many applications, the enzyme content will be as high as possible or practicable.

5 The content of enzyme (calculated as pure enzyme protein) in a granule of the invention will typically be in the range of from about 0.5% to 50% by weight of the enzyme-containing granule.

Auxiliary granulation agents

10 The granules of the invention particularly contains auxiliary granulation agents for purposes such as aiding the formation of granules, controlling density and volume of granules, controlling amount of active compound in the granules, stabilising the active compound and the like.

15 Auxiliary granulating agents may include but is not limited to:

a) Fillers such as fillers conventionally used in the field of granulation e.g. water soluble and/or insoluble inorganic salts such as finely ground alkali sulphate, alkali carbonate and/or
20 alkali chloride), clays such as kaolin (e.g. Speswhite™, English China Clay), bentonites, talcs, zeolites, and/or silicates.

b) Binders such as binders conventionally used in the field of granulation e.g. binders with a high melting point or no melting
25 point at all and of a non waxy nature e.g. polyvinyl pyrrolidon, dextrins, polyvinylalkohol, cellulose derivatives, for example hydroxypropyl cellulose, methyl cellulose or CMC. A suitable binder is a carbohydrate binder such as Glucidex 21D available from Roquette Freres, France.

210319-145001
c) Fiber materials such as fibers conventionally used in the field of granulation. Pure or impure cellulose in fibrous form can be sawdust, pure fibrous cellulose, cotton, or other forms of pure or impure fibrous cellulose. Also, filter aids based on fibrous cellulose can be used. Several brands of cellulose in fibrous form are on the market, e.g. CEPO and ARBOCELL. In a publication from Svenska Trämjolsfabrikerna AB, "Cepo Cellulose Powder" it is stated that for Cepo S/20 cellulose the approximate maximum fiber length is 500 μm , the approximate average fiber length is 160 μm , the approximate maximum fiber width is 50 μm and the approximate average fiber width is 30 μm . Also, it is stated that CEPO SS/200 cellulose has an approximate maximum fiber length of 150 μm , an approximate average fiber length of 50 μm , an approximate maximum fiber width of 45 μm and an approximate average fiber width of 25 μm . Cellulose fibers with these dimensions are very well suited for the purpose of the invention. The words "Cepo" and "Arbocel" are Trademarks. Particular fibrous cellulose is ArbocelTM BFC200. Also synthetic fibres may be used as described in EP 304331 B1 and typical fibres may be made of polyethylene, polypropylene, polyester, especially nylon, polyvinylformat, poly(meth)acrylic compounds.

d) Liquid agents such as conventionally used in the field of granulation. A liquid agent is used in conventional mixer granulation processes for enabling the build up or agglomeration of the conventional granulating component particles into granules. The liquid agent is water and/or a waxy substance. The liquid agent is always used in a liquid phase in the granulation process but may later on solidify; the waxy substance if present, therefore, is either dissolved or dispersed in the water or melted. By the term "waxy substance" as used herein is meant a

substance which possesses all of the following characteristics 1) the melting point is between 30 and 100°C, particularly between 40 and 60°C, 2) the substance is of a tough and not brittle nature, and 3) the substance possesses a certain plasticity at room temperature. Both water and waxy substance are liquid agents, i.e. they are both active during the formation of the granules; the waxy substance stays as a constituent in the finished granules, whereas the majority of the water is removed during a drying step. Examples of waxy substances are polyglycols, fatty alcohols, ethoxylated fatty alcohols, mono-, di- and triglycerolesters of higher fatty acids, e.g. glycerol monostearate, alkylarylethoxylates, and coconut monoethanolamide.

If a high amount of waxy substance is used, relatively little water should be added, and vice versa. Thus, the liquid agent can be either water alone, waxy substance alone or a mixture of water and waxy substance. When a mixture of water and waxy substance is used the water and the waxy substance can be added in any sequence, e.g. first the water and then the waxy substance, or first the waxy substance and then the water or a solution or suspension of the waxy substance in the water. Also, when a mixture of water and waxy substance is used, the waxy substance can be soluble or insoluble (but dispersible) in water. If water is used a liquid agent it may not be a part of the finished mixer granule as usually most of the water is dried off at a subsequent drying of the mixer granules.

e) Enzyme stabilizing or protective agents such as conventionally used in the field of granulation. Stabilizing or protective agents may fall into several categories: alkaline or neutral materials, reducing agents, antioxidants and/or salts of first transition series metal ions. Each of these may be used in conjunction with other protective agents of the same or different categories.

Examples of alkaline protective agents are alkali metal silicates, -carbonates or bicarbonates, which provide a chemical scavenging effect by actively neutralizing e.g. oxidants. Examples of reducing protective agents are salts of sulfite, 5 thiosulfite or thiosulfate, while examples of antioxidants are methionine, butylated hydroxytoluene (BHT) or butylated hydroxyanisol (BHA). Most particular agents are salts of thiosulfates, e.g. sodium thiosulfate. Also enzyme stabilizers may be borates, borax, formates, di- and tricarboxylic acids and 10 reversible enzyme inhibitors such as organic compounds with sulfhydryl groups or alkylated or arylated boric acids.

f) Cross linking agents such as conventionally used in the field of granulation. Cross linking agents may be enzyme-compatible 15 surfactants e.g. ethoxylated alcohols, especially ones with 10 to 80 ethoxy groups.

Further, suspension agents, mediators (for boosting bleach action upon dissolution of the granule in e.g. a washing application or mediators for enzymes) and/or solvents may be 20 incorporated as auxiliary granulating agents.

Coating agents

The coating comprises one or more conventional coating agents components such as described in WO 89/08694, WO 89/08695, EP 270 608 B1 and/or WO 00/01793. Other examples of coating agents may 25 be found in US 4,106,991, EP 170360, EP 304332, EP 304331, EP 458849, EP 458845, WO 97/39116, WO 92/12645A, WO 89/08695, WO 89/08694, WO 87/07292, WO 91/06638, WO 92/13030, WO 93/07260, WO 93/07263, WO 96/38527, WO 96/16151, WO 97/23606, US 5,324,649, US 4,689,297, EP 206417, EP 193829, DE 4344215, DE 4322229 A, DD 30 263790, JP 61162185 A and/or JP 58179492. Especially the salt

coatings described in WO 00/01793 are useful for coatings in the present invention.

The coating agent may be selected from the list of auxiliary granulation agents described, *supra*. Further coating agents may be selected the following non-limiting list of polymers, chlorine scavengers, plasticizers, pigments, lubricants (such as surfactants or antistatic agents) and fragrances.

Polymers useful in coating layers include vinyl polymers or vinyl co-polymers such as polyvinyl alcohol (PVA) and/or polyvinyl pyrrolidone or derivatives thereof. Also included are isoptalic acid polymers.

Plasticizers useful in coating layers in the context of the present invention include, for example: polyols such as sugars, sugar alcohols, or polyethylene glycols (PEGs) having a molecular weight less than 1000; urea, phthalate esters such as dibutyl or dimethyl phthalate; and water.

Suitable pigments include, but are not limited to, finely divided whiteners, such as titanium dioxide or kaolin, coloured pigments, water soluble colorants, as well as combinations of one or more pigments and water soluble colorants.

As used in the present context, the term "lubricant" refers to any agent, which reduces surface friction, lubricates the surface of the granule, decreases tendency to build-up of static electricity, and/or reduces friability of the granules. Lubricants can also play a related role in improving the coating process, by reducing the tackiness of binders in the coating. Thus, lubricants can serve as anti-agglomeration agents and wetting agents. Examples of suitable lubricants are polyethylene glycols (PEGs) and ethoxylated fatty alcohols.

In embodiments aimed primarily at granules for detergent formulations, different "functional" components could be added

to the coating such as TAED, CMC, bleach, OBA, surfactants, perfume as well as other functional components used in detergent formulations known to the person skilled in the art. The coating may also optionally comprise functional components selected for
5 their specific use in the, pharmaceutical industry, agriculture, foodstuffs industry, baking industry, additives industry, feed industry, detergents industry or other industries where granules comprising a biologically active compound can be used.

In a particular embodiment of the invention the granule of
10 the invention is coated with a protective coating having a high constant humidity of at least 81% such as described in WO 89/08694, which is hereby incorporated by reference. Accordingly, the coating should, in certain embodiments, act as a moisture and/or bleach barrier to stabilise the biologically
15 active compound in the core. Furthermore, in alternative embodiments, the coating unit acts as a mechanical barrier during mechanical processes such as dosing or tabletting. In certain embodiments, the coating unit is sufficiently compressible and flexible for the core to withstand a tabletting
20 process, both in a structural sense and with regards to biological activity of the active compound. This is potentially most applicable for detergent formulations.

In a particular embodiment the coating agent absorbs light from the excitation source and/or emitted from a fluorescent
25 marker in the granule, so that when an area of the granule surface is coated with the coating agent a reduction in detected light emitted from this area is achieved.

The fluorescent marker

30 The fluorescent marker comprised the granular composition of the invention may be any compound exhibiting fluorescence when being

illuminated. The fluorescent marker is particularly organic and exhibiting fluorescence when illuminated with light in the X-ray, ultra violet and/or visible regions of the electromagnetic spectrum, e.g. light having wavelengths between 10-700 nm, more
5 particular light in the ultra violet region, i.e. 10-380 nm.

Furthermore, the fluorescent marker comprised the granular composition of the invention is capable upon excitation to emit light in the ultra violet, visible and/or near infrared regions of the electromagnetic spectrum, i.e. suitably between 185-2600
10 nm.

The fluorescent marker may belong to the group of biologically active compounds, auxiliary granulation agents and coating agents or it may be a compound added to the granular composition with the sole purpose of performing the fluorescence
15 analysis of the invention. It is however from a cost saving point of view preferred that the fluorescent marker is the biologically active compound itself or it is an auxiliary granulation agent.

Depending on the property of the granulated composition to
20 be evaluated by the fluorescence analysis, e.g. dust properties or coating thickness, different fluorescent marker may be chosen. For evaluation of dust properties it is for example more suitable to chose the biologically active compound as the fluorescent marker because it is necessary to assess the amount
25 of potentially damaging active compound in dust particles present in the granular composition, while for evaluation of coating thickness it may be possible to choose a suitable auxiliary granulation agent as fluorescent marker.

In the case the biologically active compound is the
30 fluorescent marker, especially those belonging to the particular group of proteins and/or peptides, in which it is aromatic amino acids residues such as tyrosine and tryptophan that are

responsible for the fluorescence emission, it is preferred, in the fluorescence analysis, to illuminate the granular composition with a light source delivering ultra violet light (UV-light), particularly delivering a substantial portion of UV-
5 light having wavelengths between 10-380 nm, more particularly between 200-400 nm or 200-300 nm, most particularly between 260-280 nm. In this case it is further preferred to detect only emitted light in the range of 200-700 nm, such as from 400-700 nm, or from 300-400 nm, especially light from 280-360 nm or from
10 325-375 nm. Also, in this case it is required to choose a detector, such as a CCD camera, capable of detecting emitted light having these wavelengths.

In case the fluorescent marker is one of the auxiliary granulation agents, it is preferred, in the fluorescence
15 analysis, to illuminate to granular composition with a light source delivering light having wavelengths between 350-550 nm, more particularly between 375-425 nm. Also in this case it is required to choose a detector, such as a CCD camera, capable of detecting emitted light having these wavelengths. In the process
20 of making granules one may also add a fluorescent marker to the process, which only serves the purpose of being a fluorescent marker for the fluorescence analysis. A wide range of suitable fluorescent compound are available e.g. from Molecular Probes, USA.

25 **Fluorescence analysis in granulation and coating processes**

The present invention also encompass processes for preparing granular compositions comprising a biologically active compound and optionally auxiliary granulation agents in a granulation apparatus using the above mentioned method of fluorescence
30 analysis to predict properties of the granular composition and control and improve the preparation process.

Accordingly, the present invention provides a process for preparing granules comprising a biologically active compound and optionally auxiliary granulation agents in a granulation apparatus said process comprising the step of performing
5 fluorescence analysis on a fluorescent marker comprised in the granular composition as described, *supra*, on the granules forming in the granulator.

In a particular embodiment the fluorescence analysis is carried out during the formation of granules in the granulation
10 process, particularly on-line, meaning that the fluorescence analysis is performed more than one time in real time during the granulation process with a suitable rate of repetition. The repetition rate will, *inter alia*, depend on the data processing of data from the detector(s). In the particular embodiment of
15 using CCD or ICCD cameras about 15 measurements of the emitted light per second is recorded in form of two-dimensional images in the granulation process. The term "formation of granules" includes also coating granules with a coating layer. In this embodiment the process also particularly comprises the step of
20 changing at least one process parameter as a result of the fluorescence analysis. The process parameter to be changed may be any parameter influencing the granulation process and/or the properties of the formed granules. These parameters may be supply of granulation material, i.e. biologically active
25 compound and/or auxiliary granulation agents and/or coating agent to the granulator, supply of gas to the granulator, temperature in the granulator, pressure in the granulator, pH in the granulator and mechanical force conferred to the granulation material. The process parameter may be changed manually or
30 though an automated system, cf. granulation apparatus.

In a further embodiment fluorescence analysis in accordance with the invention may also suitably be used to control dusting

properties of finished granular compositions after granulation. Accordingly, the invention further provides a method for fluorescence analysis of active dust in a granular composition comprising a biologically active compound. Using this method, 5 granular compositions, which do not meet the desired quality with respect to dust, may be discarded or reprocessed.

In a further additional embodiment fluorescence analysis in accordance with the invention may also suitably be used to control coating thickness and/or homogeneity of finished 10 granular compositions after granulation. Accordingly, the invention further provides a method for fluorescence analysis of coating thickness in a composition of coated granules comprising a biologically active compound. Using this method granular compositions, which do not meet the desired quality with respect 15 to coating thickness may be discarded or reprocessed.

The imaging system can, as said be used for evaluation of a quality parameter, such as active dust values or coating thickness. In one embodiment the evaluation is performed on-line during for example a coating process. The evaluation is 20 performed by recording, in a particular by means of a camera, images of emitted light from granules subjected to an excitation light source and comparing the recorded images with images recorded of samples (reference samples) with known values of a quality parameter. The fluorescent images of the reference 25 samples and the corresponding quality parameters are used to provide a calibration model, such as a Partial Least Square model or any other modelling system suitable for making calibration models of image data. The model may then used to predict estimates of a quality parameter from the fluorescent 30 images of an unknown sample.

Thus the present invention also includes a method for estimating a quality parameter of a granular composition

comprising a purified biologically active comprising the steps of:

- a) providing a calibration model by illuminating a granular composition comprising a purified biologically active compound having a known quality parameter with light capable of fluorescence excitation of a fluorescent marker comprised in the granular composition, recording one or more images of the light emitted from the granular composition of a known quality and subjecting recorded images to data processing, particularly in the form of partial least squares data processing, to form a calibration model,
- b) illuminating a unknown granular composition comprising a purified biologically active compound with light capable of fluorescence excitation of a fluorescent marker comprised in the granular composition, recording at least one image of the light emitted from the unknown granular composition,
- c) comparing at least one image of the unknown granular composition with the calibration model and
- d) estimating the quality parameter of the unknown granular composition.

Granulation apparatus

Also included in the scope of the invention is a granulation and/or coating apparatus comprising means for performing fluorescence analysis on granular compositions in accordance with the invention. Accordingly, the invention provides a granulation or coating apparatus comprising:

particular embodiment this device is a band pass filter or a grate monochromator. In one embodiment one or more filtering devices are positioned so that only the emitted light is filtered and so that the emitted light must pass the filter(s) before reaching the detector(s). In another embodiment at least two filtering devices are positioned so that both the illuminating light and the emitted light is filtered. Most preferred filters are those selecting wavelength as described for the particular fluorescent markers, *supra*. In the case two detectors are used the optical arrangement also includes at least one beam splitter such as dichroic mirrors.

In a most particular embodiment the optical arrangement includes a stroboscope light source, 2 CCD camera detectors, one band pass filter for filtering illumination light, two band pass filters for filtering emitted light, lenses and two dichroic mirror beam splitters as depicted in figure 1.

In one particular embodiment the projecting means include means for projecting illuminating light through an opening in the chamber onto a portion of material being processed in the chamber and projecting emitted light from this material in the chamber to the detector.

In a more particular embodiment the granulation apparatus further comprise means for providing a purge stream of material from the chamber. In this case the optical arrangement is positioned to allow fluorescence analysis of material in the purge stream rather than on material present in the chamber. One reason for preferring this embodiment is that granulation processes usually involves considerable wear and tear of the granulation equipment. When granulating a biologically active compound such as an enzyme, some auxiliary granulation agents may be clays or other inorganic substances. These substances may have a significant sanding effect on the granulation equipment.

Accordingly, when granulating in e.g. a mixer it is not unusual to observe that several millimetres of steel is sanded off the surfaces on the interior parts of the granulation equipment per year. This magnitude of wear and tear may be very detrimental to the sensitive equipment of the optical arrangement. The granules in the purge stream may suitably be recycled and this way the fluorescence analysis does not interfere with the granulation process. The purge stream may suitably lead the granules past a part of the purge stream transparent to light wherein the projection of light may occur. As an example the purge stream may be transported from the granulation chamber, through a transporting system, which e.g. may include one or more elements selected from chutes, pumps, pipe, conveyor belts, cyclones and the like, to the optical arrangement. The fluorescence analysis may suitably occur at a point in the transporting system, where the granulated product can be accessed by the illuminating light, and from which point the emitted light may reach the detector(s). For example such point may be a point where part of e.g. a pipe material is replaced with a transparent material such as glass, quartz or a polymeric material. Particularly, at the point where the fluorescence analysis occurs the means for providing the purge stream includes means for forming a single layer of granules, so that no or little overlapping occurs in the detection from granules, which superimpose each other at the moment of detection. This may be achieved by loading the granulated product onto a tilted (non-horizontal) vibrating surface (e.g. a vibrating chute), where the area of the surface, the speed at which the granules are loaded, and the transport speed of the granules over the vibrating surface (the tilting angle) are adjusted so that the area of the shaking surface is always larger than the area of the granules present on the surface. This way the granules will form a substantial single

analysis. A control unit may be a PLC or other equipment capable of receiving data from a computing unit and converting these data into output controlling one or more hardware devices influencing the granulation process, such as feed streams, speed, temperature, airflows etc.

The procedure for carrying out the present is demonstrated in the following experiments. The experiments are only examples of one embodiment of the invention and should in no way be interpreted as limiting to the scope of the invention.

EXAMPLES

Example 1

Fluorescence analysis on raw materials for making enzyme granules:

Fluorescence analysis of eight different raw materials for enzyme granulation and enzyme concentrate were measured on a LS50B (Perkin Elmer) instrument. The raw materials were excited with light of the internal source of different wavelengths from 230-500 nm in 10 nm steps and emission from the materials was recorded from 270-700 nm in steps of 1 nm. Slit gap in the Perkin Elmer instrument for both excitation and emission was 4 nm. The fluorescence was measured by illuminating the raw material placed in a quartz container (cuvette) and measuring fluorescence emission from the raw materials at an angle displaced 22.5 degrees from the direction of the illuminating light as required by the instrument design.

Several raw materials fluoresced significantly but the enzyme concentrate had a uniquely a very intensive emission at about 350 nm.

Example 2

Fluorescence analysis on enzyme granules

Fluorescence analysis of uncoated enzyme granules as well as coated granules were measured on a LS50B (Perkin Elmer) instrument. The granules were excited with light of the internal source of different wavelengths from 230-500 nm in 10 nm steps and emission from the materials was recorded from 270-700 nm in steps of 1 nm. Slit gap in the Perkin Elmer instrument for both excitation and emission was 4 nm. The fluorescence was measured by illuminating the raw material placed in a quartz container (cuvette) and measuring fluorescence emission from the raw materials at an angle displaced 22.5 degrees from the direction of the illuminating light as required by the instrument design.

The results showed a peak of emission around 350 nm corresponding to the enzyme concentrate. Another strong peak occurred between 450-500 nm due to fluorescent compounds among granulation auxiliaries. The results show the feasibility of detecting enzymes in the granules.

Example 3

On-line fluorescence analysis of granules:

Fluorescence analysis of uncoated enzyme granules as well as coated granules was measured on using a optical arrangement as shown in figure 1. Two camera detectors of the type Donpisha "Progressive Camera Module" XC-8500CE 1/2" ITCCD 782(H) x 582(V), with a CCIR Additional 35 mm lens at sample introduction point was used. The light source was an Oriel Xenon Flash Lamp 60000 w/ Oriel attachment 60008 and Oriel Power Supply 68826. Illuminating light was filtered using a band pass filter to

produce a beam of light having a wavelength of 450 nm. Before reaching the cameras the emitted light was split into two beams by a dichroic mirror beam splitter and each beam was filtered by a band pass filters. One filter allowed passage of 530 nm light (green filter) and the other filter allowed passage of 620 nm light (red filter).

The illumination and detection of emitted light was carried out by loading enzyme granules into a funnel having an outlet of proportion allowing passage of the granules and performing the analysis on granules leaving the funnel immediately after the funnel outlet.

The signal from the detectors was transferred to a computing unit (ordinary personal computer) equipped with data acquisition hardware, DAQ and SCB-68 breadboard and image processing software, Labview 4.1.1 IMAQ vision and All-purpose Labview all from National Instruments to produce instantaneous digital images of fluorescent granules passing the beam of illuminating light.

These measurements resulted in a series of images which were recorded and could be played back as a motion picture. Uncoated granules fluoresced brightly and the form and shape of the granules were clearly depicted, thus demonstrating the feasibility of using fluorescence analysis in preparing enzyme granules. For coated granules the fluorescence was significantly reduced showing that the coating layer reduced the access to the fluorescent marker. Darker areas of the recording thus indicated granules with thicker coatings, thus demonstrating the feasibility of using fluorescence analysis in preparing coated granules.

Example 4

Fluorescence analysis of enzyme granules with varying enzyme concentration:

5 An experiment was performed to evaluate if the biologically active could also be the fluorescent marker. Four batches with varying contents of purified protease concentrate were fabricated in a Lödige mixer. The contents of protease were 0 (reference), 1, 4 and 12 KPNU, respectively where KPNU is Kilo
10 NOVO Protease Units, which is determined relatively to a protease standard, and the determination is based on the digestion of a dimethyl casein (DMC) solution by the proteolytic enzyme at standard conditions, i.e. 50°C, pH 8.3, 9 min. reaction time, 3 min. measuring time.

15 The samples were excited with an Oriel Xenon Flash Lamp 60000 w/ Oriel attachment 60008 and Oriel Power Supply 68826. Illuminating light was filtered using a band pass filter to produce a beam of light in the region 300-400 nm. The emitted light was detected with a 3-CCD camera from JAI (M-90). The
20 camera was mounted with a Computar 55 Telecentric lens. The signal from the detectors was transferred to a computing unit (ordinary personal computer) equipped with IFC51 frame grabber and Image-Pro Plus version 4.5.

Fluorescent images recorded of the granules showed visually that
25 the average intensity of emitted light increased significantly as a function of increasing concentrations of purified protease. The four batches of granules were subsequently coated with a standard PEG-coating (PEG4000) containing kaolin and titanium dioxide. Fluorescent images recorded of the coated granules
30 showed visually that the average intensity of emitted light increased as a function of increasing concentrations of purified protease.

This indicates that the biologically active, in this experiment a protease, may also be the fluorescent marker.

Example 5

5

Fluorescence analysis of enzyme granules with varying thickness of coating:

An experiment was performed to investigate whether there is a correlation between the thickness of the coating and the
10 intensity of emitted light. A standard batch of granules containing an enzyme was coated with a PEG-coating (PEG4000) containing kaolin and titan dioxide. The coating was sprayed onto the granules (Hüttlin) and samples of granules were withdrawn from the process when 10 %, 25 % and 50 %, respectively, of the coating had been administered.

15 The samples were excited with an Oriel Xenon Flash Lamp 60000 w/ Oriel attachment 60008 and Oriel Power Supply 68826.

Illuminating light was filtered using a band pass filter to produce a beam of light in the region from 300-400 nm. The
20 emitted light was detected with a 3-CCD camera from JAI (M-90). The camera was mounted with a Computar 55 Telecentric lens. The signal from the detectors was transferred to a computing unit (ordinary personal computer) equipped with IFC51 frame grabber and Image-Pro Plus version 4.5.

25 Fluorescent images recorded of the coated granules showed visually that the average intensity of emitted light decreased for increasing concentrations of coating (i.e. for 10%, 25% and 50% of coating administered).

This indicates that the intensity of fluorescent emitted light
30 can be used to predict the thickness of the coating.

Example 6

Fluorescence analysis of enzyme granules with varying amounts of enzymatic active dust:

An experiment was performed to evaluate if fluorescence analysis
5 could be used to estimate the amount of dust. A priori it is known that coated enzyme granules with scars in the coating lead to problem with enzymatic active dust.

Eight samples with protease active dust values from 29 ng/g to 2420 ng/g of protease per gram of dust were submitted to on-line
10 fluorescence analysis.

The samples were excited with an Oriel Xenon Flash Lamp 60000 w/ Oriel attachment 60008 and Oriel Power Supply 68826.

10054.012
20054.012
30054.012
40054.012
50054.012
60054.012
70054.012
80054.012
90054.012
10054.012
11054.012
12054.012
13054.012
14054.012
15054.012
16054.012
17054.012
18054.012
19054.012
20054.012
21054.012
22054.012
23054.012
24054.012
25054.012
26054.012
27054.012
28054.012
29054.012
30054.012
31054.012
32054.012
33054.012
34054.012
35054.012
36054.012
37054.012
38054.012
39054.012
40054.012
41054.012
42054.012
43054.012
44054.012
45054.012
46054.012
47054.012
48054.012
49054.012
50054.012
51054.012
52054.012
53054.012
54054.012
55054.012
56054.012
57054.012
58054.012
59054.012
60054.012
61054.012
62054.012
63054.012
64054.012
65054.012
66054.012
67054.012
68054.012
69054.012
70054.012
71054.012
72054.012
73054.012
74054.012
75054.012
76054.012
77054.012
78054.012
79054.012
80054.012
81054.012
82054.012
83054.012
84054.012
85054.012
86054.012
87054.012
88054.012
89054.012
90054.012
91054.012
92054.012
93054.012
94054.012
95054.012
96054.012
97054.012
98054.012
99054.012
10054.012
101054.012
102054.012
103054.012
104054.012
105054.012
106054.012
107054.012
108054.012
109054.012
110054.012
111054.012
112054.012
113054.012
114054.012
115054.012
116054.012
117054.012
118054.012
119054.012
120054.012
121054.012
122054.012
123054.012
124054.012
125054.012
126054.012
127054.012
128054.012
129054.012
130054.012
131054.012
132054.012
133054.012
134054.012
135054.012
136054.012
137054.012
138054.012
139054.012
140054.012
141054.012
142054.012
143054.012
144054.012
145054.012
146054.012
147054.012
148054.012
149054.012
150054.012
151054.012
152054.012
153054.012
154054.012
155054.012
156054.012
157054.012
158054.012
159054.012
160054.012
161054.012
162054.012
163054.012
164054.012
165054.012
166054.012
167054.012
168054.012
169054.012
170054.012
171054.012
172054.012
173054.012
174054.012
175054.012
176054.012
177054.012
178054.012
179054.012
180054.012
181054.012
182054.012
183054.012
184054.012
185054.012
186054.012
187054.012
188054.012
189054.012
190054.012
191054.012
192054.012
193054.012
194054.012
195054.012
196054.012
197054.012
198054.012
199054.012
20054.012
201054.012
202054.012
203054.012
204054.012
205054.012
206054.012
207054.012
208054.012
209054.012
210054.012
211054.012
212054.012
213054.012
214054.012
215054.012
216054.012
217054.012
218054.012
219054.012
220054.012
221054.012
222054.012
223054.012
224054.012
225054.012
226054.012
227054.012
228054.012
229054.012
230054.012
231054.012
232054.012
233054.012
234054.012
235054.012
236054.012
237054.012
238054.012
239054.012
240054.012
241054.012
242054.012
243054.012
244054.012
245054.012
246054.012
247054.012
248054.012
249054.012
250054.012
251054.012
252054.012
253054.012
254054.012
255054.012
256054.012
257054.012
258054.012
259054.012
260054.012
261054.012
262054.012
263054.012
264054.012
265054.012
266054.012
267054.012
268054.012
269054.012
270054.012
271054.012
272054.012
273054.012
274054.012
275054.012
276054.012
277054.012
278054.012
279054.012
280054.012
281054.012
282054.012
283054.012
284054.012
285054.012
286054.012
287054.012
288054.012
289054.012
290054.012
291054.012
292054.012
293054.012
294054.012
295054.012
296054.012
297054.012
298054.012
299054.012
30054.012
301054.012
302054.012
303054.012
304054.012
305054.012
306054.012
307054.012
308054.012
309054.012
310054.012
311054.012
312054.012
313054.012
314054.012
315054.012
316054.012
317054.012
318054.012
319054.012
320054.012
321054.012
322054.012
323054.012
324054.012
325054.012
326054.012
327054.012
328054.012
329054.012
330054.012
331054.012
332054.012
333054.012
334054.012
335054.012
336054.012
337054.012
338054.012
339054.012
340054.012
341054.012
342054.012
343054.012
344054.012
345054.012
346054.012
347054.012
348054.012
349054.012
350054.012
351054.012
352054.012
353054.012
354054.012
355054.012
356054.012
357054.012
358054.012
359054.012
360054.012
361054.012
362054.012
363054.012
364054.012
365054.012
366054.012
367054.012
368054.012
369054.012
370054.012
371054.012
372054.012
373054.012
374054.012
375054.012
376054.012
377054.012
378054.012
379054.012
380054.012
381054.012
382054.012
383054.012
384054.012
385054.012
386054.012
387054.012
388054.012
389054.012
390054.012
391054.012
392054.012
393054.012
394054.012
395054.012
396054.012
397054.012
398054.012
399054.012
40054.012
401054.012
402054.012
403054.012
404054.012
405054.012
406054.012
407054.012
408054.012
409054.012
410054.012
411054.012
412054.012
413054.012
414054.012
415054.012
416054.012
417054.012
418054.012
419054.012
420054.012
421054.012
422054.012
423054.012
424054.012
425054.012
426054.012
427054.012
428054.012
429054.012
430054.012
431054.012
432054.012
433054.012
434054.012
435054.012
436054.012
437054.012
438054.012
439054.012
440054.012
441054.012
442054.012
443054.012
444054.012
445054.012
446054.012
447054.012
448054.012
449054.012
450054.012
451054.012
452054.012
453054.012
454054.012
455054.012
456054.012
457054.012
458054.012
459054.012
460054.012
461054.012
462054.012
463054.012
464054.012
465054.012
466054.012
467054.012
468054.012
469054.012
470054.012
471054.012
472054.012
473054.012
474054.012
475054.012
476054.012
477054.012
478054.012
479054.012
480054.012
481054.012
482054.012
483054.012
484054.012
485054.012
486054.012
487054.012
488054.012
489054.012
490054.012
491054.012
492054.012
493054.012
494054.012
495054.012
496054.012
497054.012
498054.012
499054.012
50054.012
501054.012
502054.012
503054.012
504054.012
505054.012
506054.012
507054.012
508054.012
509054.012
510054.012
511054.012
512054.012
513054.012
514054.012
515054.012
516054.012
517054.012
518054.012
519054.012
520054.012
521054.012
522054.012
523054.012
524054.012
525054.012
526054.012
527054.012
528054.012
529054.012
530054.012
531054.012
532054.012
533054.012
534054.012
535054.012
536054.012
537054.012
538054.012
539054.012
540054.012
541054.012
542054.012
543054.012
544054.012
545054.012
546054.012
547054.012
548054.012
549054.012
550054.012
551054.012
552054.012
553054.012
554054.012
555054.012
556054.012
557054.012
558054.012
559054.012
560054.012
561054.012
562054.012
563054.012
564054.012
565054.012
566054.012
567054.012
568054.012
569054.012
570054.012
571054.012
572054.012
573054.012
574054.012
575054.012
576054.012
577054.012
578054.012
579054.012
580054.012
581054.012
582054.012
583054.012
584054.012
585054.012
586054.012
587054.012
588054.012
589054.012
590054.012
591054.012
592054.012
593054.012
594054.012
595054.012
596054.012
597054.012
598054.012
599054.012
60054.012
601054.012
602054.012
603054.012
604054.012
605054.012
606054.012
607054.012
608054.012
609054.012
610054.012
611054.012
612054.012
613054.012
614054.012
615054.012
616054.012
617054.012
618054.012
619054.012
620054.012
621054.012
622054.012
623054.012
624054.012
625054.012
626054.012
627054.012
628054.012
629054.012
630054.012
631054.012
632054.012
633054.012
634054.012
635054.012
636054.012
637054.012
638054.012
639054.012
640054.012
641054.012
642054.012
643054.012
644054.012
645054.012
646054.012
647054.012
648054.012
649054.012
650054.012
651054.012
652054.012
653054.012
654054.012
655054.012
656054.012
657054.012
658054.012
659054.012
660054.012
661054.012
662054.012
663054.012
664054.012
665054.012
666054.012
667054.012
668054.012
669054.012
670054.012
671054.012
672054.012
673054.012
674054.012
675054.012
676054.012
677054.012
678054.012
679054.012
680054.012
681054.012
682054.012
683054.012
684054.012
685054.012
686054.012
687054.012
688054.012
689054.012
690054.012
691054.012
692054.012
693054.012
694054.012
695054.012
696054.012
697054.012
698054.012
699054.012
70054.012
701054.012
702054.012
703054.012
704054.012
705054.012
706054.012
707054.012
708054.012
709054.012
710054.012
711054.012
712054.012
713054.012
714054.012
715054.012
716054.012
717054.012
718054.012
719054.012
720054.012
721054.012
722054.012
723054.012
724054.012
725054.012
726054.012
727054.012
728054.012
729054.012
730054.012
731054.012
732054.012
733054.012
734054.012
735054.012
736054.012
737054.012
738054.012
739054.012
740054.012
741054.012
742054.012
743054.012
744054.012
745054.012
746054.012
747054.012
748054.012
749054.012
750054.012
751054.012
752054.012
753054.012
754054.012
755054.012
756054.012
757054.012
758054.012
759054.012
760054.012
761054.012
762054.012
763054.012
764054.012
765054.012
766054.012
767054.012
768054.012
769054.012
770054.012
771054.012
772054.012
773054.012
774054.012
775054.012
776054.012
777054.012
778054.012
779054.012
780054.012
781054.012
782054.012
783054.012
784054.012
785054.012
786054.012
787054.012
788054.012
789054.012
790054.012
791054.012
792054.012
793054.012
794054.012
795054.012
796054.012
797054.012
798054.012
799054.012
80054.012
801054.012
802054.012
803054.012
804054.012
805054.012
806054.012
807054.012
808054.012
809054.012
810054.012
811054.012
812054.012
813054.012
814054.012
815054.012
816054.012
817054.012
818054.012
819054.012
820054.012
821054.012
822054.012
823054.012
824054.012
825054.012
826054.012
827054.012
828054.012
829054.012
830054.012
831054.012
832054.012
833054.012
834054.012
835054.012
836054.012
837054.012
838054.012
839054.012
840054.012
841054.012
842054.012
843054.012
844054.012
845054.012
846054.012
847054.012
848054.012
849054.012
850054.012
851054.012
852054.012
853054.012
854054.012
855054.012
856054.012
857054.012
858054.012
859054.012
860054.012
861054.012
862054.012
863054.012
864054.012
865054.012
866054.012
867054.012
868054.012
869054.012
870054.012
871054.012
872054.012
873054.012
874054.012
875054.012
876054.012
877054.012
878054.012
879054.012
880054.012
881054.012
882054.012
883054.012
884054.012
885054.012
886054.012
887054.012
888054.012
889054.012
890054.012
891054.012
892054.012
893054.012
894054.012
895054.012
896054.012
897054.012
898054.012
899054.012
90054.012
901054.012
902054.012
903054.012
904054.012
905054.012
906054.012
907054.012
908054.012
909054.012
910054.012
911054.012
912054.012
913054.012
914054.012
915054.012
916054.012
917054.012
918054.012
919054.012
920054.012
921054.012
922054.012
923054.012
924054.012
925054.012
926054.012
927054.012
928054.012
929054.012
930054.012
931054.012
932054.012
933054.012
934054.012
935054.012
936054.012
937054.012
938054.012
939054.012
940054.012
941054.012
942054.012
943054.012
944054.012
945054.012
946054.012
947054.012
948054.012
949054.012
950054.012
951054.012
952054.012
953054.012
954054.012
955054.012
956054.012
957054.012
958054.012
959054.012
960054.012
961054.012
962054.012
963054.012
964054.012
965054.012
966054.012
967054.012
968054.012
969054.012
970054.012
971054.012
972054.012
973054.012
974054.012
975054.012
976054.012
977054.012
978054.012
979054.012
980054.012
981054.012
982054.012
983054.012
984054.012
985054.012
986054.012
987054.012
988054.012
989054.012
990054.012
991054.012
992054.012
993054.012
994054.012
995054.012
996054.012
997054.012
998054.012
999054.012
100054.012
1001054.012
1002054.012
1003054.012
1004054.012
1005054.012
1006054.012
1007054.012
1008054.012
1009054.012
1010054.012
1011054.012
1012054.012
1013054.012
1014054.012
1015054.01